

## SAFETY DATA SHEET

According to OSHA Hazcom Standard 29 CFR 1910.1200

### Nitrogen 0.1 cmol/mol and 7 others mix / Methane

Date of issue: 2022-08-30

Revision date: 2020-01-16

Version: 3.0

#### 1. IDENTIFICATION

##### A. Product name

- Nitrogen 0.1 cmol/mol and 7 others mix / Methane

##### B. Recommended use and restriction on use

- General use : Not available  
- Restriction on use : Not available

##### C. Manufacturer / Supplier / Distributor information

###### o Manufacturer information

- Company name : RIGAS Co.,Ltd  
- Address : 46,Munpyeongseo-ro 17 beon-gil, Daedeok-gu,Daejeon, KOREA  
- Emergency telephone number : 82-42-934-6900

###### o Supplier/Distributor information

- Company name : RIGAS Co.,Ltd  
- Address : 46,Munpyeongseo-ro 17 beon-gil, Daedeok-gu,Daejeon, KOREA  
- Emergency telephone number : 82-42-934-6900

#### 2. HAZARD IDENTIFICATION

##### A. GHS Classification

- Flammable gases : Category1  
- Gases under pressure : Compressed gas  
- Germ cell mutagenicity : Category1B  
- Carcinogenicity : Category1A

##### B. GHS label elements

###### o Hazard symbols



###### o Signal words

- Danger

###### o Hazard statements

- H220 Extremely flammable gas  
- H280 Compressed gas ; Contains gas under pressure; may explode if heated  
- H340 May cause genetic defects  
- H350 May cause cancer

###### o Precautionary statements

###### 1) Prevention

- P201 Obtain special instructions before use.  
- P202 Do not handle until all safety precautions have been read and understood.  
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

###### 2) Response

- P308+P313 If exposed or concerned: Get medical advice/attention.  
- P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

- P381 Eliminate all ignition sources if safe to do so.

### 3) Storage

- P403 Store in a well-ventilated place.
- P405 Store locked up.
- P410+P403 Protect from sunlight. Store in a well-ventilated place.

### 4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

## C. Other hazards which do not result in classification

- Not available

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Methane	Methyl hydride ; Fire damp	74-82-8	Balance
Carbon dioxide	Carbonic acid anhydride ; DRY ICE ; Carbonic acid gas ; Carbonic anhydride ;	124-38-9	4.55
Ethane	Not available	74-84-0	4.2
Propane	Dimethylmethane ; Propyl hydride ; n-Propane ; Propyldihydride ;	74-98-6	1.98
Butane	N-Butane ; Butyl hydride ; Methylenehydride ;	106-97-8	0.29
2-Methylpropane	Propane, 2-methyl- ; 1,1-Dimethylethane ; i-Butane ; iso-Butane ; Trimethylmethane ;	75-28-5	0.26
Nitrogen	Nitrogen, Elemental ; Diazyne ; Dinitrogen ; Diatomic nitrogen ;	7727-37-9	0.1
Pentane	Amyl hydride ; Normal pentane ; N-Pentane ;	109-66-0	0.01
2-Methylbutane	Butane, 2-methyl- (TSCA, DSL, ENCS, AICS, SWISS, PICCS, ASIA-PAC, NZIoC) ; 2-Methylbutane (English, French) (DSL, EINECS, ECL) ; 2-Methylbutan (german) (EINECS) ; 2-metilbutano (spanish) (EINECS) ; ISOPENTAN (german) (SWISS) ; ISOPENTANE (PICCS) ; BUTANE,2-METHYL (PICCS) ; 1,1,2-Trimethylethane ; Borger Isopentane ; Ethyl dimethyl methane ; Exxsol Isopentane S ; iso-Pentane ; Isoamyl hydride ; Methylbutane ; Isopentane ; 2-Methylbutane ; Ethyldimethylmethane	78-78-4	0.01

## 4. FIRST AID MEASURES

### A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.

### B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.
- Get medical attention immediately.
- Remove contaminated clothing, shoes and isolate.
- Wear gloves when washing the patient, and please avoid contact with contaminated clothing.

### C. Inhalation contact

- Take specific treatment if needed.
- When exposed to large amounts of steam and mist, move to fresh air.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.

### D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.
- Get medical attention immediately.

## E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

#### **F. Notes to physician**

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

### **5. FIREFIGHTING MEASURES**

#### **A. Suitable (Unsuitable) extinguishing media**

- Avoid use of water jet for extinguishing
- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray

#### **B. Specific hazards arising from the chemical**

- Compressed gas ; Contains gas under pressure; may explode if heated
- Extremely flammable gas
- May cause cancer
- May cause genetic defects

#### **C. Special protective actions for firefighters**

- Avoid inhalation of materials or combustion by-products.
- Cool containers with water until well after fire is out.
- Do not approach the tank surrounded by fire until it is extinguished.
- In case of conflagration, use automatic fire sprinkler. Major fire may require withdrawal, allowing the object itself to burn.
- Keep unauthorized personnel out.

### **6. ACCIDENTAL RELEASE MEASURES**

#### **A. Personal precautions, protective equipment and emergency procedures**

- Do not touch spilled material. Stop leak if you can do it without risk.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment
- Move container to safe area from the leak area.
- Must work against the wind, let the upwind people to evacuate.
- Remove all sources of ignition.

#### **B. Environmental precautions**

- If large amounts have been spilled, inform the relevant authorities.
- Prevent runoff and contact with waterways, drains or sewers.

#### **C. Methods and materials for containment and cleaning up**

- Appropriate container for disposal of spilled material collected.
- Disposal of waste shall be in compliance with the Wastes Control Act
- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notify the central and local government if the emission reach the standard threshold.

### **7. HANDLING AND STORAGE**

#### **A. Precautions for safe handling**

- Avoid contact with incompatible materials.
- Avoid direct physical contact.
- Comply with all applicable laws and regulations for handling
- Dealing only with a well-ventilated place.
- Do not handle until all safety precautions have been read and understood.

#### **B. Conditions for safe storage, including any incompatibilities**

- Avoid direct sunlight.
- Check regularly for leaks.
- Do not apply any physical shock to container.
- Do not apply direct heat.
- Do not use damaged containers.

### **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**A. Exposure limits**

- **ACGIH TLV**
  - [Methane] : Asphyxia
  - [Carbon dioxide] : TWA 5000 ppm (Asphyxia), STEL 30,000 ppm
  - [Ethane] : Asphyxia
  - [Propane] : Asphyxia
  - [Butane] : STEL 1000 ppm
  - [2-Methylpropane] : STEL 1000 ppm
  - [Nitrogen] : Asphyxia
  - [Pentane] : TWA, 1000 ppm (2950 mg/m<sup>3</sup>)
  - [2-Methylbutane] : TWA, 1000 ppm (2950 mg/m<sup>3</sup>)
- **OSHA PEL**
  - [Carbon dioxide] : 9000
  - [Propane] : 1800
  - [Pentane] : 2950

**B. Engineering controls**

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

**C. Individual protection measures, such as personal protective equipment**

- **Respiratory protection**
  - Consider warning properties before use.
  - Respiratory protection is ranked in order from minimum to maximum.
- **Eye protection**
  - Provide an emergency eye wash station and quick drench shower in the immediate work area.
  - Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- **Hand protection**
  - Wear appropriate chemical resistant glove.
- **Skin protection**
  - Wear appropriate chemical resistant protective clothing.
- **Others**
  - Not available

**9. PHYSICAL AND CHEMICAL PROPERTIES**

A. Appearance	<b>CH<sub>4</sub></b>
- Appearance	gas
- Color	Colorless
B. Odor	odorless
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	-183 °C
F. Initial Boiling Point/Boiling Ranges	-161 °C
G. Flash point	Not available
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Flammable gas
J. Upper/Lower Flammability or explosive limits	15 / 5 %
K. Vapour pressure	466000 mmHg (25°C)
L. Solubility	0.0022 g/100ml (25°C)
M. Vapour density	0.554 (air = 1)
N. Specific gravity	Not available
O. Partition coefficient of n-octanol/water	1.09
P. Autoignition temperature	537 °C
Q. Decomposition temperature	Not available
R. Viscosity	0.01087 cP (20°C)
S. Molecular weight	16.04

A. Appearance	<b>CO<sub>2</sub></b>
---------------	-----------------------

- Appearance	Liquid
- Color	Gas, liquid: colorless solid: white
B. Odor	Odorless
C. Odor threshold	Not available
D. pH	3.7-3.2
E. Melting point/Freezing point	-56.6 °C (at 5.2 ATM)
F. Initial Boiling Point/Boiling Ranges	-78.5 °C
G. Flash point	Not available
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	Not available
K. Vapour pressure	48300 mmHg (at 25 °C)
L. Solubility	0.145 g / ml (water at 25 C)
M. Vapour density	1.522 (21C)
N. Specific gravity	1.527 ((gas, air = 1))
O. Partition coefficient of n-octanol/water	0.83
P. Autoignition temperature	Not available
Q. Decomposition temperature	>1700 C
R. Viscosity	Not available
S. Molecular weight	44.01

A. Appearance	<b>C2H6</b>
- Appearance	gas
- Color	Colorless
B. Odor	odorless
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	-172 °C
F. Initial Boiling Point/Boiling Ranges	-88 °C
G. Flash point	Not available
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Flammable gas
J. Upper/Lower Flammability or explosive limits	12.5 / 3 %
K. Vapour pressure	31459 mmHg (25°C)
L. Solubility	0.00602 g/100ml (25°C)
M. Vapour density	1.05 (air=1)
N. Specific gravity	Not available
O. Partition coefficient of n-octanol/water	1.81
P. Autoignition temperature	472 °C
Q. Decomposition temperature	Not available
R. Viscosity	0.00634 cP (-78.5°C)
S. Molecular weight	30.08

A. Appearance	<b>C3H8</b>
- Appearance	gas
- Color	Colorless
B. Odor	Peculiar smell
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	190 °C
F. Initial Boiling Point/Boiling Ranges	-42 °C
G. Flash point	-105 °C
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	9.5 / 2.1 %
K. Vapour pressure	7150 mmHg (at 25 °C)
L. Solubility	Not available
M. Vapour density	1.55 ((air=1))

N. Specific gravity	0.5853 (at -45 °C (water=1))
O. Partition coefficient of n-octanol/water	2.36
P. Autoignition temperature	450 °C
Q. Decomposition temperature	Not available
R. Viscosity	Not available
S. Molecular weight	44.11

A. Appearance	<b>iso-C4H10</b>
- Appearance	Gas
- Color	Colorless
B. Odor	Petroleum odor
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	-138.3 °C
F. Initial Boiling Point/Boiling Ranges	-11.7 °C
G. Flash point	Not available
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Flammable gas
J. Upper/Lower Flammability or explosive limits	8.4 / 1.8 %
K. Vapour pressure	2611 mmHg (25°C)
L. Solubility	0.00489 g/100mℓ (25°C)
M. Vapour density	2.01 (air = 1)
N. Specific gravity	0.6 (Water = 1, liquid)
O. Partition coefficient of n-octanol/water	2.76
P. Autoignition temperature	460 °C (Closed cup)
Q. Decomposition temperature	Not available
R. Viscosity	0.238 cP (-10°C)
S. Molecular weight	58.12

A. Appearance	<b>n-C4H10</b>
- Appearance	Etc.
- Color	Not available
B. Odor	Unpleasant odor
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	-138 °C
F. Initial Boiling Point/Boiling Ranges	-0.5 °C
G. Flash point	-60 °C
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	8.4 / 1.8 %
K. Vapour pressure	1600 mmHg (21.1 °C)
L. Solubility	0.006 g/100mℓ (25°C)
M. Vapour density	2.1
N. Specific gravity	0.6
O. Partition coefficient of n-octanol/water	2.89
P. Autoignition temperature	365 °C
Q. Decomposition temperature	Not available
R. Viscosity	Not available
S. Molecular weight	Not available

A. Appearance	<b>iso-C5H12</b>
- Appearance	Liquid
- Color	Colorless
B. Odor	Alcohol odor
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	-160 °C

F. Initial Boiling Point/Boiling Ranges	28 °C
G. Flash point	<-51 °C (C.C.)
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	7.6 / 1.4%
K. Vapour pressure	79 kPa (20 °C)
L. Solubility	0.0048 g/100 mL (25 °C)
M. Vapour density	2.5 (air = 1)
N. Specific gravity	0.6 (Water = 1)
O. Partition coefficient of n-octanol/water	2.3
P. Autoignition temperature	420 °C
Q. Decomposition temperature	Not available
R. Viscosity	Not available
S. Molecular weight	72.2

A. Appearance	<b>n-C5H12</b>
- Appearance	Liquid
- Color	Colorless
B. Odor	Gasoline odor
C. Odor threshold	2.2 ppm
D. pH	Not available
E. Melting point/Freezing point	-129 °C
F. Initial Boiling Point/Boiling Ranges	36 °C
G. Flash point	-49 °C (c.c.)
H. Evaporation rate	28.6 (butyl acetate = 1)
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	7.8 / 1.5%
K. Vapour pressure	53.3 mm Hg (18.5 °C)
L. Solubility	38 mg / l (25 °C)
M. Vapour density	2.5
N. Specific gravity	0.63
O. Partition coefficient of n-octanol/water	3.39
P. Autoignition temperature	309 °C
Q. Decomposition temperature	Not available
R. Viscosity	0.289 cP (0 °C)
S. Molecular weight	72.15

A. Appearance	<b>N2</b>
- Appearance	gas
- Color	Colorless
B. Odor	odorless
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	-210 °C
F. Initial Boiling Point/Boiling Ranges	-196 °C
G. Flash point	Not available
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	Not available
K. Vapour pressure	1 atm (77.347 deg K)
L. Solubility	(1.18E+004mg/L(25°C))
M. Vapour density	0.97 ((air = 1))
N. Specific gravity	0.808 (kg / l at the boiling point of the liquid)
O. Partition coefficient of n-octanol/water	0.67
P. Autoignition temperature	Not available
Q. Decomposition temperature	Not available
R. Viscosity	Not available
S. Molecular weight	28

## 10. STABILITY AND REACTIVITY

### A. Chemical Stability

- high-pressure gas; May explode when heated.
- May form explosive mixture.

### B. Possibility of hazardous reactions

- Contact with other combustible material may cause fire.
- Cylinders exposed to fire may vent and release flammable gas.

### C. Conditions to avoid

- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with incompatible materials and condition.
- Avoid contact with heat, sparks, flame or other ignition sources.

### D. Incompatible materials

- Not available

### E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

## 11. TOXICOLOGICAL INFORMATION

### A. Information on the likely routes of exposure

- **Respiratory tracts**
  - Not available
- **Oral**
  - Not available
- **Eye/Skin**
  - Not available

### B. Delayed and immediate effects and also chronic effects from short and long term exposure

- **Acute toxicity**
  - \* **Oral**
    - Product (ATEmix) : Not available
    - [Pentane] : LD50>2000 mg/kg Rat (ECHA)
  - \* **Dermal**
    - Product (ATEmix) : Not available
    - [2-Methylbutane] : LD50 > 2000 mg/kg Rat (OSHR)
  - \* **Inhalation**
    - Product (ATEmix) : Not available
    - [Methane] : Gas LC50 353553 ppm 4 hr (LC50 500000 2 hr) Mouse (RTECS)
    - [Carbon dioxide] : Gas LCLo 90000 ppm 5 min Other(Mammal human, LCLo, 90000ppm/5M, ChemIDplus)
    - [Ethane] : Gas LC50 > 200000ppm/4hr (800000ppm/15min) Rat (Read-across CAS No. 74-98-6)(ECHA), LC50 658 mg/ℓ 4 hr Rat (KOSHA)
    - [Propane] : LC50 142500 ppm/4hr (570000 ppm/15min) Rat (ECHA)
    - [Butane] : Gas LC50 > 200000ppm 4hr Rat (conversion of 800000ppm 15min) (Read-across CAS No. 74-98-6) (ECHA)
    - [2-Methylpropane] : LC50 > 13023ppm 4hr No death, Not classified (ECHA)
    - [Pentane] : LC50 364 mg/L/4 hr Rat (HSDB, ChemIDPlus)
    - [2-Methylbutane] : Steam LC50 = 280 mg/ℓ 4 hr Rat (Hazardous substances: Galogenated hydrocarbons) Bandman A.L. et al., Chimia, 1990.
- **Skin corrosion/irritation**
  - Not available
- **Serious eye damage/irritation**
  - Not available
- **Respiratory sensitization**
  - Not available
- **Skin sensitization**
  - Not available



- **Carcinogenicity**
  - \* **IARC**
    - Not available
  - \* **OSHA**
    - Not available
  - \* **ACGIH**
    - Not available
  - \* **NTP**
    - Not available
  - \* **EU CLP**
    - [Butane] : Carc.1A (butane (containing  $\geq 0.1\%$  butadiene (203-450-8)))
    - [2-Methylpropane] : Carc.1A (isobutane (containing  $\geq 0.1\%$  butadiene (203-450-8)))
- **Germ cell mutagenicity**
  - May cause genetic defects
- **Reproductive toxicity**
  - Not available
- **STOT-single exposure**
  - Not available
- **STOT-repeated exposure**
  - Not available
- **Aspiration hazard**
  - Not available

## 12. ECOLOGICAL INFORMATION

### A. Ecotoxicity

- **Fish**
  - [Carbon dioxide] : LC50 35 mg/l 96 hr Other (Rainbow trout) (HSDB)
  - [Propane] : LC50 > 100 mg/l 96 hr (Species : Fish TLM) (IUCLID)
  - [Butane] : LC50 27.98 mg/l 96 hr Other (Read across, Estimate)
  - [Pentane] : LC50 4.26 mg/l 96 hr Oncorhynchus mykiss (Semi-static, OECD Guideline 203, GLP) (ECHA)
  - [2-Methylbutane] : LC50 4.26 mg/L 96h (ECHA)
- **Crustaceans**
  - [Methane] : LC50 164.244 mg/l 48 hr (Estimate)
  - [Propane] : LC50 52.157 mg/l 48 hr (Estimate)
  - [Butane] : LC50 69.43 mg/l 48 hr Daphnia sp. (Read across, Estimate)
  - [Pentane] : LC50 9.1 mg/l 48 hr Daphnia magna(static) (ECHA)
  - [2-Methylbutane] : EC50 = 2.3 mg/l 48 hr Daphnia magna (NITE: IUCLID, 2000)
- **Algae**
  - [Methane] : EC50 95.717 mg/l 96 hr (Estimate)
  - [Propane] : LC50 32.252 mg/l 96 hr (Estimate)
  - [Butane] : EC50 16.47 mg/l 96 hr Green algae (Read across, Estimate)
  - [Pentane] : ErC50 10.7 mg/l 72 hr Selenastrum capricornutum(static, OECD Guideline 201, GLP) (ECHA)

### B. Persistence and degradability

- **Persistence**
  - [Methane] : log Pow 1.09 (ECHA)
  - [Carbon dioxide] : log Kow 0.83 (IUCLID)
  - [Ethane] : log Kow 1.81
  - [Propane] : log Kow 2.36
  - [Butane] : log Kow 2.89 (HSDB)
  - [2-Methylpropane] : log Kow = 2.76 (HSDB)
  - [Nitrogen] : log Kow 0.67 (NLM/HSDB)
  - [Pentane] : log Kow 3.45 (ECHA)
  - [2-Methylbutane] : log Kow=4 (25C)(ECHA)
- **Degradability**
  - Not available

### C. Bioaccumulative potential

- **Bioaccumulative potential**

- [Methane] : BCF 1 (HSDB)
- [Carbon dioxide] : No bioaccumulation (IUCLID)
- [Propane] : BCF 13 (HSDB)
- [2-Methylpropane] : BCF = 30 (estimate)(HSDB)
- [Pentane] : BCF 171 (Estimate) (ECHA)

- **Biodegradation**

- [Methane] : 65.7 (%) 35 d (IUCLID)
- [Ethane] : 65.7 (%) 35 day (Aerobic, Microorganism, readily biodegradable)
- [Propane] : 65.7 (%) 35 day
- [Butane] : 100% 385.5 hr (Read across, ECHA)
- [2-Methylpropane] : Biodegradability = 65.7 (%) 35 day (Aerobic, Microorganism, readily biodegradable)(HSDB)
- [Pentane] : 87 (%) 28 day (OECD Guideline 301 F, GLP) (ECHA)
- [2-Methylbutane] : 71.43% 28 days (ECHA)

#### **D. Mobility in soil**

- Not available

#### **E. Other adverse effects**

- [Pentane] : Algae(Scenedesmus capricornutum): NOErC(72h) 7.51mg/L (OECD Guideline 201, GLP) (ECHA)

### **13. DISPOSAL CONSIDERATIONS**

#### **A. Disposal methods**

- It shall be treated by incineration
- Oil water separation technology shall be applied as pre-waste treatment if it is applicable
- Stabilization and minimization treatment by incineration or similar method can be applied, if more than two kinds of designated wastes are in mixture state and it is impractical to separate them

#### **B. Special precautions for disposal**

- Anyone with business license number who generates industrial wastes shall treat the waste by him/herself or by entrusting to the legal entities who treat the wastes, recycle the wastes of others or install and operate the waste treatment facilities according to the Wastes Control Act
- Dispose of waste in accordance with all applicable laws and regulations.

### **14. TRANSPORT INFORMATION**

#### **A. UN No. (IMDG)**

- 1954

#### **B. Proper shipping name**

- COMPRESSED GAS, FLAMMABLE, N.O.S.

#### **C. Hazard Class**

- 2.1

#### **D. IMDG CODE/IATA DGR Packing group**

- Not applicable

#### **E. Marine pollutant**

- Not applicable

#### **F. Special precautions for user related to transport or transportation measures**

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-D (Flammable gases)
- EmS SPILLAGE SCHEDULE : S-U (Gases (flammable, toxic or corrosive))

### **15. REGULATORY INFORMATION**

#### **A. National and/or international regulatory information**

- **POPs Management Law**

- [Methane] : Not applicable
- [Carbon dioxide] : Not applicable
- [Ethane] : Not applicable
- [Propane] : Not applicable
- [Butane] : Not applicable
- [2-Methylpropane] : Not applicable
- [Nitrogen] : Not applicable
- [Pentane] : Not applicable
- [2-Methylbutane] : Not applicable

- **Information of EU Classification**

- \* **Classification**

- [Methane] : H220,H280
    - [Ethane] : H220,H280
    - [Propane] : H220,H280
    - [Butane] : H220,H280,H340,H350
    - [2-Methylpropane] : H220,H280,H340,H350
    - [Pentane] : H225,H304,H336,H411
    - [2-Methylbutane] : H224,H304,H336,H411

- **U.S. Federal regulations**

- \* **OSHA PROCESS SAFETY (29CFR1910.119)**

- Not applicable

- \* **CERCLA Section 103 (40CFR302.4)**

- Not applicable

- \* **EPCRA Section 302 (40CFR355.30)**

- Not applicable

- \* **EPCRA Section 304 (40CFR355.40)**

- Not applicable

- \* **EPCRA Section 313 (40CFR372.65)**

- Not applicable

- **Rotterdam Convention listed ingredients**

- Not applicable

- **Stockholm Convention listed ingredients**

- Not applicable

- **Montreal Protocol listed ingredients**

- Not applicable

## 16. OTHER INFORMATION

### A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

### B. Issue date

- 2022-08-30

### C. Revision number and Last date revised

- 3 times, 2020-01-16

### D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).